

Table II (1 of 3)
Identification of Achievable Performance Standards
Source Category: Polyester Resin Operations

Rule/Measure	Rule/Measure				
	BAAQMD Rule 8-50 Polyester Resin Operations Last Revised 12/20/95	ColAPCD Rule 2-37 VOC Control Measure for Polyester Resin Operations Last Revised 1/23/96	SACAQMD Rule 465 Polyester Resin Operations Last Revised 2/6/97	SBAPCD Rule 349 Polyester Resin Operations Last Revised 4/27/93	SCAQMD Rule 1162 Polyester Resin Operations Last Revised 5/13/94
Exemptions	Touch-up and repair are exempt from process requirements of 8-50-301.	Touch-up and repair are exempt from process requirements of section 3.	Only record keeping requirements apply when the volume of polyester resin materials used is < 20 gallons/month.	Addition or use of styrene provided that <50 gallons/calendar year is used. However, must maintain records of total styrene used per calendar year.	None.
Applicability	Manufacturing of products using polyester resins.	All commercial, military, and industrial sources performing polyester resin operations.	Persons who operate polyester resin operations within Sacramento County.	All commercial and industrial polyester resin operations.	All polyester resin operations that fabricate, rework, repair, or touch-up products for commercial, military, or industrial use.
Comments		Has the same compound exemptions as Yolo Solano 2.30.		This rule applies to ROC, which in the comparisons was assumed to be equivalent to VOC. Has the same compound exemptions as San Joaquin 4684.	

S:\DRAT\WEBDOCS\POLY2_1.WP6